

# *NowExam*

Higher Quality , Better Service !



# Q&A

<http://www.nowexam.com>

We offer free update service for one year.

**Exam** : **000-175**

**Title** : IBM WebSphere Lombardi  
Edition V7.2, Development  
(Entry)

**Version** : DEMO

1.What is the correct JavaScript syntax to initialize a local variable named contact of a complex type Contact?

- A. `contact = new Contact();`
- B. `tw.local.contact = new Contact();`
- C. `tw.local.contact = new tw.local.Contact();`
- D. `tw.local.contact = new tw.object.Contact();`

**Answer: D**

2.The service "Get Request ID" needs to know the number of existing requests of a particular type in order to generate an ID for the request. It uses a nested service named "Get Request Count" for this purpose. What can be determined about data mapping?

- A. The type of the request is an output variable of the 'Get Request ID' service.
- B. The unique ID for the request is an input variable to the 'Get Request ID' service.
- C. The number of existing requests of a particular type is an input variable to the 'Get Request Count' service.
- D. The 'Get Request ID' service has a private variable that maps to the output from 'Get Request Count' service.

**Answer: D**

3.An application has five pieces of data: `creditScore`, `newHomeAddress`, `amountToBorrow`, `creditApproved`, and `appraisalPassed`. The data is organized in a complex variable, `loanApp`. How should the developer reference the credit score?

- A. `tw.local.creditScore`
- B. `tw.loanApp.creditScore`
- C. `tw.local.loanApp.creditScore`
- D. `tw.local.approveCredit.loanApp.creditScore`

**Answer: C**

4.A bank has a home loan process containing an 'Approve Credit' activity with a service attached with the same name. During the activity 'Approve Credit', a credit check is done and credit approval is based on the amount to be borrowed and the borrower's credit score. The loan application has five pieces of data: creditScore, newHomeAddress, amountToBorrow, creditApproved, and appraisalPassed. The data is organized in a complex variable, loanApp. What is the minimum output from the 'Approve Credit' service?

- A. loanApp
- B. creditApproved
- C. appraisalPassed
- D. amountToBorrow

**Answer: B**

5.What is the default visibility property for all new controls?

- A. Hidden
- B. Editable
- C. Disabled
- D. Required

**Answer: B**

6.A developer needs to build the Coach shown in the following Exhibit.

The image shows a web form titled "Lombardi Coach". On the left, there is a sidebar with a user icon and the label "Coach". The main content area has a header "Lombardi Coach" and a sub-header "Contact". Below the sub-header, there are two columns: "Personal Information" and "Contact Details". The "Personal Information" column contains fields for "Name:" and "Birth Date:". The "Contact Details" column contains fields for "Phone:", "Mobile:", and "Email:". A "Submit" button is located at the bottom right of the form.

What is the minimum number of sections the developer needs to create in the Coach?

- A. 1
- B. 2
- C. 3
- D. 4

**Answer: D**

7. For each section on a Coach, there is an HTML table generated in the background. How are table rows dynamically defined or allocated? Based on the:

- A. number of sections on the Coach.
- B. number of Controls added to each section.
- C. entry specified on the customization property.
- D. Table Override property in the Presentation category.

**Answer: B**

8. A developer was asked to create a Coach based on the company's form for processing a new employee. For a copy of the company's form, refer to the Exhibit below.



9. An activity is defined as a conditional activity, and a script that returns a Boolean is written in the text box in the Condition tab. What will happen if the script returns true?

- A. The activity will be skipped.
- B. The activity will be performed.
- C. The activity will be performed if it is added to `tw.system.process.selectedConditionalActivities`.
- D. The activity will be skipped even if the activity is added to `tw.system.process.selectedConditionalActivities`.

**Answer: B**

10. To add a custom Coach XSL transformation to artifacts in a process application, the XSL file should be added as:

- A. a managed file.
- B. a localization resource.
- C. an installation service.
- D. process application settings.

**Answer: A**